


Silicon Carbide Power MOSFET (N-Channel Enhancement)

V_{DS}	1200V
$I_D(25^\circ C)$	63A
$R_{DS(on)}$	40mΩ



Features

- High speed switching
- Essentially no switching losses
- Reduction of heat sink requirements
- Maximum working temperature at 175 °C
- High blocking voltage
- Fast Intrinsic diode with low recovery current
- High-frequency operation
- Halogen free, RoHS compliant
- AEC-Q101 qualified

Typical Applications

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

Mechanical Data

- **Package:** TO-247AB
- **Terminals:** Tin plated leads
- **Polarity:** As marked

■ Maximum Ratings ($T_c=25^\circ C$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE	TEST CONDITIONS	NOTE
Device marking code				D212040NCTG1	
Drain source voltage @ $T_j=25^\circ C$	$V_{DS,max}$	V	1200	$V_{GS}=0 V, I_D=100\mu A$	
Gate source voltage @ $T_j=25^\circ C$	$V_{GS,max}$	V	-10/+22	Absolute maximum values	
Gate source voltage @ $T_j=25^\circ C$	$V_{GS,op}$	V	-5/+18	Recommended operational values	Note 1、2
Continuous drain current @ $T_c=25^\circ C$	I_D	A	63	$V_{GS}=18V, T_c=25^\circ C$	Fig.18
Continuous drain current @ $T_c=100^\circ C$			41	$V_{GS}=18V, T_c=100^\circ C$	
Pulsed drain current	$I_{D(pulsed)}$	A	160	Pulse width t_p limited by $T_{j,max}$	Fig.23
Avalanche energy, Single Pulse	E_{AS}	mJ	650	$V_{DD}=75V, L=10mH$	
Power Dissipation	P_{TOT}	W	333	$T_c=25^\circ C, T_j = 175^\circ C$	Fig.17
Power Dissipation			144	$T_c=110^\circ C, T_j = 175^\circ C$	
Operating junction and Storage temperature range	T_j, T_{stg}	°C	-55 to +175		
Soldering temperature	T_L	°C	260	1.6mm (0.063") from case for 10s	
Mounting torque	T_M	Nm	0.6	M3 screw Maximum of mounting process: 3	



■ Static Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Gate threshold voltage	V _{GS(th)}	V	2.0	2.5	4.0	V _{DS} =V _{GS} , I _D = 10mA	Fig.4, 11
				2.0		V _{DS} =V _{GS} , I _D = 10mA, T _j =175°C	
Drain source breakdown voltage	V _{(BR)DSS}	V	1200			V _{GS} =0, I _D =100uA	
Zero gate voltage drain current	I _{DSS}	uA		1	10	V _{DS} =1200V, V _{GS} = 0V	Fig.16
Gate source leakage current	I _{GSS}	nA			100	V _{GS} = 18V, V _{DS} =0V	
Current drain source on-state resistance	R _{DS ON}	mΩ		42	52	V _{GS} =18V, I _D =40A	Fig.5, 6, 7
				72		V _{GS} =18V, I _D =40A, T _j =175°C	
Internal gate resistance	R _g	Ω		1.8	5.0	f=1MHz	
Diode forward voltage	V _{SD}	V		4.0		V _{GS} =-5V, I _{SD} =20A	Fig.8
				3.4		V _{GS} =0V, I _{SD} =20A T _j =175°C	Fig.9
Transconductance	g _f	S		18		V _{DS} =20V, I _D =40A	Fig.4
				17		V _{DS} =20V, I _D =40A, T _j =175°C	

■ Dynamic Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Input capacitance	C _{iss}	pF		2225		V _{DS} =1000V, V _{GS} =0V, T _j =25°C, f=1MHz, V _{AC} = 25mV	Fig.13, 14
Output capacitance	C _{oss}			141			
Reverse capacitance	C _{rss}			15			
C _{oss} stored energy	E _{oss}	uJ		78			Fig.15
Gate source charge	Q _{gs}	nC		34		V _{DS} =800V, V _{GS} =-5/18V, I _D =40A	Fig.12
Gate drain charge	Q _{gd}			42			
Gate charge	Q _g			120			

■ Switching Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Turn on switching energy	E _{on}	uJ		932.6		V _{DD} =800V, V _{GS} =-5/+18V, I _D =40A, R _g =2.7Ω, L=100uH	Fig.21, 20
Turn off switching energy	E _{off}			151.6			
Turn on delay time	t _{d(on)}	ns		17.5			

Rise time	t_r			37			
Turn off delay time	$t_{d(off)}$	ns		22.4		$V_{DD}=800V, V_{GS}=-5/+18V, I_D=40A, R_g=2.7\Omega, L=100\mu H$	Fig.21, 20
Fall time	t_f			14.6			

■Body diode characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Diode forward voltage	V_{SD}	V		4.0		$V_{GS}=-5V, I_{SD}=20A$	Fig.8
				3.4		$V_{GS}=0V, I_{SD}=20A, T_j=175^\circ C$	Fig.9
Continuous diode forward current	I_s	A		60		$T_c=25^\circ C$	Note1
Reverse recovery time	trr	nS		54		$V_R=800V, V_{GS}=-5V, I_D=40A, dI/dt=1000A/\mu s$	
Reverse recovery charge	Qrr	nC		283			
Peak reverse recovery current	$Irrm$	A		15			

Note 1: When using SiC Body Diode the maximum recommended $V_{GS} = -5V$

Note 2: MOSFET can also safely operate at 0/18 V

■Thermal Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Typ.
Thermal resistance	$R_{\theta J-C}$	$^\circ C / W$	0.45


■Typical Characteristics


Figure 1. Output Characteristics $T_j = -55^\circ C$




Figure 2. Output Characteristics $T_j = 25^\circ C$




Figure 3. Output Characteristics $T_j = 175^\circ\text{C}$




Figure 4. Transfer Characteristics for various junction temperature




Figure 5. On-resistance vs. temperature for various gate voltage




Figure 6. Normalized on-resistance vs. temperature




Figure 7. On-resistance vs. drain current




Figure 8. Body diode characteristic at $T_j = 25^\circ\text{C}$




Figure 9. Body diode characteristic




Figure 10. 3rd quadrant characteristic at $T_j = 25^\circ\text{C}$




Figure 11. Threshold voltage vs. temperature




Figure 12. Gate charge characteristic




Figure 13. Capacitances vs. drain source voltage (0-1000V)




Figure 14. Capacitances vs. drain source voltage (0-200V)




Figure 15. Output capacitor stored energy




Figure 16. Reverse characteristics vs. Tj




Figure 17. Maximum power dissipation derating vs. case temperatere




Figure 18. Continuous drain current derating vs. case temperatere




Figure 19. Transient thermal impedance (junction - case)




Figure 20. Clamped Inductive switching energy vs. darin current




Figure 21. Clamped inductive switching energy vs. R_g




Figure 22 Safe Operating Area




Figure 23 Switching Times Definition





Figure 24 Clamped Inductive Switching Waveform Test Circuit

■Outline Dimensions



TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
ΦP	3.40	3.80
ΦP1	-	7.30
S	6.15TYP	
H1	5.44TYP	
b3	2.80	3.20



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.