


**Silicon Carbide Power MOSFET (N-Channel Enhancement)**

V_{DS}	1200V
$I_D(25^\circ C)$	33A
$R_{DS(on)}$	80mΩ

**Features**

- High speed switching
- Essentially no switching losses
- Reduction of heat sink requirements
- Maximum working temperature at 175 °C
- High blocking voltage
- Fast Intrinsic diode with low recovery current
- High-frequency operation
- Halogen free, RoHS compliant

Typical Applications

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

Mechanical Data

- **Package:** TO-247AB
- **Terminals:** Tin plated leads
- **Polarity:** As marked

■Maximum Ratings ($T_c=25^\circ C$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	VALUE	TEST CONDITIONS	NOTE
Device marking code				D212080NCTGH	
Drain source voltage @ $T_j=25^\circ C$	$V_{DS,max}$	V	1200	$V_{GS}=0 V, I_D=100\mu A$	
Gate source voltage @ $T_j=25^\circ C$	$V_{GS,max}$	V	-10/+25	Absolute maximum values (AC f > 1Hz, duty cycle < 1%)	Note1
Gate source voltage @ $T_j=25^\circ C$	$V_{GS,op}$	V	-5/+20	Recommended operational values	
Continuous drain current @ $T_c=25^\circ C$	I_D	A	33	$V_{GS}=20V, T_c=25^\circ C$	Fig.14
Continuous drain current @ $T_c=110^\circ C$			24	$V_{GS}=20V, T_c=110^\circ C$	
Pulse Drain Current	$I_{D,pulse}$	A	81	Limited by t_{pw}	Fig.15
Avalanche energy, Single Pulse	E_{AS}	mJ	300	$V_{DD}=75V, L=25mH$	
Power Dissipation	P_{TOT}	W	224	$T_c=25^\circ C, T_j = 175^\circ C$	Fig.13
Operating junction and Storage temperature range	T_j, T_{stg}	°C	-55 to +175		
Soldering temperature	T_L	°C	260	1.6mm (0.063") from case for 10s	
Mounting torque	T_M	Nm	1.0	M3 screw Maximum of mounting process: 3	



■ Static Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Gate threshold voltage	V _{GS(th)}	V	1.5	3	4.5	V _{DS} =V _{GS} , I _D = 20mA	Fig.4, 11
Drain source breakdown voltage	V _{(BR)DSS}	V	1200			V _{GS} =0, I _D =100uA	
Zero gate voltage drain current	I _{DSS}	uA		<1	50	V _{DS} =1200V, V _{GS} = 0V	
				10		V _{DS} =1200V, V _{GS} = 0V, T _j = 175°C	
Gate source leakage current	I _{GSS}	nA			250	V _{GS} = 20V, V _{DS} =0V	
Current drain source on-state resistance	R _{DS ON}	mΩ		80	110	V _{GS} =20V, I _D =15A	Fig.3, 5, 6
				134		V _{GS} =20V, I _D =15A, T _j =175°C	
Transconductance	g _f	S		5.9		V _{DS} =20V, I _D =15A	

■ Dynamic Electrical Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Input capacitance	C _{iss}	pF		2644		V _{DS} =800V, V _{GS} =0V, T _j =25°C, f=1MHz, V _{AC} = 25mV	Fig.10
Output capacitance	C _{oss}			85			
Reverse capacitance	C _{rss}			8			
C _{oss} stored energy	E _{oss}	uJ		33			Fig.12
Gate source charge	Q _{gs}	nC		57		V _{DS} =800V, V _{GS} =-5/20V, I _D =15A	Fig.16
Gate drain charge	Q _{gd}			23			
Gate charge	Q _g			131			
Internal Gate Resistance	R _{G(int)}	Ω		2.0	5.0	f =1MHz, V _{AC} = 25mV	

■ Switching Characteristics (Tc=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Turn on delay time	t _{d(on)}	ns		16		V _{DD} =800V, V _{GS} =-5/+20V, I _D =15A, L=300uH, R _{G(ext)} = 2.7Ω	Fig.17, 18
Rise time	t _r			26.7			
Turn off delay time	t _{d(off)}			25.6			
Fall time	t _f			16			
Turn on switching energy	E _{on}	uJ		307.6			
Turn off switching energy	E _{off}			61.5			

■Body diode characteristics (T_c=25°C unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Min.	Typ.	Max.	Test Conditions	Note
Diode forward voltage	V _{SD}	V		3.7		V _{GS} =0V, I _{SD} =7.5A	Fig.8
Continuous diode forward current	I _s	A		37		V _{GS} =0V, T _c =25°C	
Reverse recovery time	t _{rr}	nS		50		V _{DS} =800V, V _{GS} =0V, I _{SD} =7.5A, di/dt=300A/uS	
Reverse recovery charge	Q _{rr}	nC		81			
Peak reverse recovery current	I _{rrm}	A		3.2			

Note 1: When using SiC Body Diode the maximum recommended V_{GS} = -5V

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Value
Thermal resistance	R _{θJ-C}	°C/W	0.67


■Typical Characteristics


Figure 1. Output Characteristics T_j = 25°C




Figure2. Output Characteristics T_j = 175°C




Figure 3. On-resistance vs. drain current




Figure 4. Transfer Characteristics for various T_j




Figure 5. On-resistance vs. gate voltage for various T_j




Figure 6. On-resistance vs. Temperature for various Gate voltage




Figure 7. Normalized On-Resistance vs. Temperature




Figure 8. Reverse Output Characteristics at T_j = 25°C









Figure 13. Maximum Power Dissipation Derating vs. Case Temperature Figure 14. Drain Current Derating vs. Case Temperature




Figure 15. Safe Operating Area




Figure 16. Gate Charge Characteristics




Figure 17. Clamped Inductive Switching Energy vs. Drain Current




Figure 18. Clamped Inductive Switching Energy vs. External Gate Resistor ($R_g(\text{ext.})$)




Figure 19. Transient Junction to Case Thermal Impedance




Figure 20. Schematic of Resistive Switching





Figure 21. Switching Times Definition

**■Outline Dimensions****TO-247AB**

TO-247AB		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.0	1.4
b2	1.91	2.21
C	0.5	0.7
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.0	13.6
E2	4.80	5.20
E3	2.30	2.70
L	19.62	20.22
L1	-	4.30
ΦP	3.40	3.80
ΦP1	-	7.30
S	6.15TYP	
H1	5.44TYP	
b3	2.80	3.20

**Disclaimer**

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.